

Maschine Nr.	1	2	3	4	5	6	7	8	9	10	11
Hersteller	Battenfeld	Engel	Demag	Engel	Engel	Engel	Demag	Battenfeld	Engel	Engel	Engel
max. Schließkraft	1000 kN	800 kN	1100 kN	1250 kN	1500 kN	1500 kN	2000 kN	2700 kN	4000 kN	1250 kN	800 kN
Schnecken ø horizontal	40 mm	45 mm	40 mm	30 mm	40 mm	40 mm	50 mm	55 mm	60/90 mm	40 mm	20 mm
Schnecken ø vertikal	-	-	-	18 mm	30 mm	35 mm	-	-	-	30 mm	22 mm
max. Spritzvolumen horizontal	231 cm <sup>3</sup>	254 cm <sup>3</sup>	210 cm <sup>3</sup>	113 cm <sup>3</sup>	251 cm <sup>3</sup>	318 cm <sup>3</sup>	410 cm <sup>3</sup>	605 cm <sup>3</sup>	1910 cm <sup>3</sup>	251 cm <sup>3</sup>	69 cm <sup>3</sup>
max. Spritzvolumen vertikal	-	-	-	25 cm <sup>3</sup>	99 cm <sup>3</sup>	135 cm <sup>3</sup>	-	-	-	99 cm <sup>3</sup>	38 cm <sup>3</sup>
Holmabstand hor.. x vert.	470 x 420	HL	470 x 470	HL	HL	460 x 460	560 x 560	710 x 630	HL	HL	HL
Aufspannplattengröße hor. x vert.	-	660 x 360	-	730 x 480	920 x 750	700 x 730	-	-	1200 x 1100	740 x 700	670 x 600
Ausfallschachtbreite	-	410 mm	-	465 mm	665 mm	-	-	-	810 mm	465 mm	450 mm
min. Werkzeugeinbauhöhe	250 mm	250 mm	250 mm	250 mm	250 mm	-	310 mm	350 mm	450 mm	400 mm	350 mm
max. Plattenabstand	750 mm	700 mm	850 mm	850 mm	950 mm	-	1335 mm	1200 mm	1450 mm	1000 mm	790 mm
max. Öffnungsweg	500 mm	450 mm	600 mm	600 mm	700 mm	-	575 mm	550 mm	1000 mm	600 mm	450 mm
Auswerferweg	150 mm	170 mm	180 mm	175 mm	175 mm	130 mm	180 mm	200 mm	250 mm	130 mm	100 mm

