

Maschine Nr.	12	13	14	15	16	17	18	19	21	22	23
Hersteller	Battenfeld	Demag	Demag	Battenfeld	Engel	Fanuc	Engel	Engel	Battenfeld	Battenfeld	Battenfeld
max. Schließkraft	400 kN	500 kN	500 kN	800 kN	800 kN	1000 kN	1000 kN	2000 kN	4500 kN	6500 kN	8000 kN
Schnecken ø horizontal	22 mm	40 mm	40 mm	40 mm	35 mm	28 mm	30 mm	45 mm	75 mm	85 mm	100 mm
Schnecken ø vertikal	-	-	-	-	-	-	-	35 mm	-	-	-
max. Spritzvolumen in PS horizontal	32 cm ³	55 cm ³	55 cm ³	201 cm ³	140 cm ³	58 cm ³	173 cm ³	280 cm ³	1310 cm ³	2200 cm ³	3050 cm ³
max. Spritzvolumen in PS vertikal	-	-	-	-	-	-	-	140 cm ³	-	-	-
Holmabstand hor. x vert.	270 x 270	370 x 370	370 x 370	370 x 370	HL	320 x 320	HL	HL	900 x 800	1000 x 1000	1120 x 1020
Aufspannplattengröße hor. x vert.	-	-	-	590 x 590	670 x 600	-	740 x 695	-	-	-	-
Ausfallschachtbreite	-	-	-	-	450 mm	-	470 mm	705 mm	-	-	-
min. Werkzeugeinbauhöhe	150 mm	210 mm	210 mm	200 mm	245 mm	150 mm	150 mm	300 mm	395 mm	500 mm	500 mm
max. Plattenabstand	800 mm	610 mm	610 mm	625 mm	695 mm	1350 mm	850 mm	1405 mm	1530 mm	1900 mm	2000 mm
max. Öffnungsweg	325 mm	400 mm	400 mm	425 mm	331 mm	900 mm	430 mm	410 mm	760 mm	1000 mm	1050 mm
Auswerferweg	100 mm	125 mm	125 mm	150 mm	100 mm	100 mm	130 mm	130 mm	250 mm	200 mm	250 mm

